User Manual
SKU: ABX00110



Description

The Modulino® Buttons, powered by an on-board STM32C011F4 microcontroller, features three SPST push buttons and three indicator LEDs. This setup enables both simple digital input reading via I2C and more advanced interfacing or reprogramming options. Ideal for projects that require user interaction, menu navigation, or quick control inputs.

Target Areas

Maker, beginner, education

Contents

1 Application Examples **3**

2 Features **4**

2.1 Contents 4

3 Related Products **4**

4 Rating **4**

4.1 Recommended Operating Conditions 4

5 Power Tree **5**

6 Block Diagram **5**

7 Functional Overview **6**

7.1 Technical Specifications (Module-Specific) 6

7.2 Pinout 7

7.3 Power Specifications 9

7.4 Mechanical Information 9

7.5 I2C Address Reference 10

7.5.1 Pull-up Resistors 11

8 Device Operation **11**

9 Certifications Summary **12**

10 Declaration of Conformity CE DoC (EU) **12**

11 Declaration of Conformity to EU RoHS & REACH 211 01/19/2021

12 Conflict Minerals Declaration **13**

13 FCC Caution **13**

1 Application Examples

- **Interactive Interfaces** Integrate multiple buttons into a project to navigate menus or adjust settings in real time.
- **Educational Projects** Teach fundamentals of state detection (pressed/released) and microcontroller-based I2C communication.
- **Control Panels** Combine button inputs with other Modulino® nodes (e.g., display, buzzer) for a complete user interface.

2 Features

- Three **SPST push buttons** and three on-board indicator LEDs.
- Integrated **STM32C011F4** microcontroller providing I2C interface by default.
- **Optional SWD** interface for custom firmware and advanced features.
- Designed for **3.3 V** operation via the Qwiic connector (I2C).
- Ideal for **user interaction** and input within modular IoT or maker projects.

2.1 Contents

SKU	Name	Purpose	Quantity
ABX00110	Modulino® Buttons	3× push buttons and indicator LEDs	1
	I2C Qwiic cable	Compatible with the Qwiic standard	1

3 Related Products

- *SKU: ASX00027* – Arduino® Sensor Kit
- *SKU: K000007* – Arduino® Starter Kit
- *SKU: AKX00026* – Arduino® Oplà IoT Kit

4 Rating

4.1 Recommended Operating Conditions

- **Microcontroller supply range:** 2.0 V – 3.6 V (STM32C011F4)
- **Powered at 3.3 V** through the Qwiic interface (in accordance with the Qwiic standard)
- **Operating temperature:** –40 °C to +85 °C

Typical current consumption:

- Push buttons + LEDs: ~2.5 mA × 3 + ~3.4 mA
- Microcontroller idle: ~3.4 mA

5 Power Tree

The power tree for the Modulino® node can be consulted below:



Modulino® Buttons Power Tree

6 Block Diagram

This module includes an STM32C011F4 microcontroller handling button inputs and LED outputs. It communicates via I2C by default, but can be reprogrammed via SWD for custom functionality.



Modulino® Buttons block diagram

7 Functional Overview

The Modulino® Buttons node has a dedicated microcontroller (STM32C011F4) which scans the three SPST push buttons and drives the three LEDs. By default, it exposes a standard I2C interface over the Qwiic connector. The on-board firmware reports button states and allows simple LED control via I2C registers. Advanced users can re-flash the microcontroller via the SWD interface for additional custom logic.

7.1 Technical Specifications (Module-Specific)

Specification	Details
Microcontroller	STM32C011F4
Accuracy	ADC: ±2 LSB typical INL
Resolution	12-bit ADC
Supply Voltage	Min: 2.0 V, Max: 3.6 V
Power Consumption	~2.5 mA × 3 + 3.4 mA (LEDs + MCU)
User Inputs	3× SPST push buttons
LEDs	3× indicator LEDs (controlled by MCU)
Communication	I2C (Qwiic), SWD (reprogramming), UART (option)

7.2 Pinout

Qwiic / I2C (1×4 Header)

Pin	Function
GND	Ground
3.3 V	Power Supply (3.3 V)
SDA	I2C Data
SCL	I2C Clock

These pads and the Qwiic connectors share the same I2C bus at 3.3 V.

Additional 1×10 Header

Pin	Function
A	Button A
GND	Ground
3V3	3.3 V Power
PF2	RESET
SWCLK	SWD Clock
SWDIO	SWD Data
TX1	USART Transmit
RX1	USART Receive
B	Button B
C	Button C

Note:

- The board can be reprogrammed via SWD to implement custom functionality.
- Pull-up resistor pads exist for optional I2C lines, but are not populated by default.





Pinout Overview

7.3 Power Specifications

- **Nominal operating voltage:** 3.3 V via Qwiic
- **Microcontroller voltage range:** 2.0 V–3.6 V

7.4 Mechanical Information



Modulino® Buttons Mechanical Information

- Board dimensions: 41 mm × 25.36 mm
- Thickness: 1.6 mm (±0.2 mm)
- Four mounting holes (Ø 3.2 mm)
  - Hole spacing: 16 mm vertically, 32 mm horizontally

7.5 I2C Address Reference

Board Silk Name	Sensor/Actuator	Modulino® I2C Address (HEX)	Editable Addresses (HEX)	Hardware I2C Address (HEX)
MODULINO BUTTONS	3× SPST Push Buttons	0x7C	Any custom address (via software config.)	0x3E

Note:

- Default I2C address is **0x7C**.
- "Hardware I2C Address" might be seen by advanced scanners, but you should use 0x7C in your code unless changed.
- A white rectangle on the bottom silk allows users to write a new address after reconfiguration.



Blank silk for identification

7.5.1 Pull-up Resistors

This module has pads for optional I2C pull-up mounting in both data lines. No resistors are mounted by default but in case the resistors are need 4.7 K resistors in an SMD 0402 format are recommended.

These are positioned between the button B and C.



Generic pull-up resistor position

8 Device Operation

By default, the board is an I2C target device. It manages button inputs and LED outputs through integrated firmware. Simply connect it to a 3.3 V Qwiic interface. If needed, you can reprogram the STM32C011F4 via SWD to modify or extend functionality. A LED positioned near each button can be controlled through the microcontroller's GPIOs PA3, PA4 and PA5.

Certifications

9 Certifications Summary

Certification	Status
CE/RED (Europe)	Yes
UKCA (UK)	Yes
FCC (USA)	Yes
IC (Canada)	Yes
RoHS	Yes
REACH	Yes
WEEE	Yes

10 Declaration of Conformity CE DoC (EU)

We declare under our sole responsibility that the products above are in conformity with the essential requirements of the following EU Directives and therefore qualify for free movement within markets comprising the European Union (EU) and European Economic Area (EEA).

11 Declaration of Conformity to EU RoHS & REACH 211 01/19/2021

Arduino boards are in compliance with RoHS 2 Directive 2011/65/EU of the European Parliament and RoHS 3 Directive 2015/863/EU of the Council of 4 June 2015 on the restriction of the use of certain hazardous substances in electrical and electronic equipment.

Substance	Maximum limit (ppm)
Lead (Pb)	1000
Cadmium (Cd)	100
Mercury (Hg)	1000
Hexavalent Chromium (Cr6+)	1000
Poly Brominated Biphenyls (PBB)	1000
Poly Brominated Diphenyl ethers (PBDE)	1000
Bis(2-Ethylhexyl) phthalate (DEHP)	1000
Benzyl butyl phthalate (BBP)	1000
Dibutyl phthalate (DBP)	1000
Diisobutyl phthalate (DIBP)	1000

Exemptions: No exemptions are claimed.

Arduino Boards are fully compliant with the related requirements of European Union Regulation (EC) 1907 /2006 concerning the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH). We declare none of the SVHCs (https://echa.europa.eu/web/guest/candidate-list-table), the Candidate List of Substances of Very High

Concern for authorization currently released by ECHA, is present in all products (and also package) in quantities totaling in a concentration equal or above 0.1%. To the best of our knowledge, we also declare that our products do not contain any of the substances listed on the "Authorization List" (Annex XIV of the REACH regulations) and Substances of Very High Concern (SVHC) in any significant amounts as specified by the Annex XVII of Candidate list published by ECHA (European Chemical Agency) 1907 /2006/EC.

12 Conflict Minerals Declaration

As a global supplier of electronic and electrical components, Arduino is aware of our obligations with regard to laws and regulations regarding Conflict Minerals, specifically the Dodd-Frank Wall Street Reform and Consumer Protection Act, Section 1502. Arduino does not directly source or process conflict minerals such as Tin, Tantalum, Tungsten, or Gold. Conflict minerals are contained in our products in the form of solder or as a component in metal alloys. As part of our reasonable due diligence, Arduino has contacted component suppliers within our supply chain to verify their continued compliance with the regulations. Based on the information received thus far we declare that our products contain Conflict Minerals sourced from conflict-free areas.

13 FCC Caution

Any Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

1. This device may not cause harmful interference.
2. This device must accept any interference received, including interference that may cause undesired operation.

FCC RF Radiation Exposure Statement:

1. This Transmitter must not be co-located or operating in conjunction with any other antenna or transmitter.
2. This equipment complies with RF radiation exposure limits set forth for an uncontrolled environment.
3. This equipment should be installed and operated with a minimum distance of 20 cm between the radiator & your body.

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

English: User manuals for license-exempt radio apparatus shall contain the following or equivalent notice in a conspicuous location in the user manual or alternatively on the device or both. This device complies with Industry Canada license-exempt RSS standard(s). Operation is subject to the following two conditions:

1. this device may not cause interference.
2. this device must accept any interference, including interference that may cause undesired operation of the device.

French: Le présent appareil est conforme aux CNR d'Industrie Canada applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux deux conditions suivantes:

1. l'appareil nedoit pas produire de brouillage.
2. l'utilisateur de l'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en compromettre le fonctionnement.

IC SAR Warning:

English: This equipment should be installed and operated with a minimum distance of 20 cm between the radiator and your body.

French: Lors de l'installation et de l'exploitation de ce dispositif, la distance entre le radiateur et le corps est d'au moins 20 cm.

Important: The operating temperature of the EUT can't exceed 85 ℃ and shouldn't be lower than -40 ℃.

Hereby, Arduino S.r.l. declares that this product is in compliance with essential requirements and other relevant provisions of Directive 2014/53/EU. This product is allowed to be used in all EU member states.

Company Information

Company name	**Arduino SRL**
Company Address	Via Andrea Appiani, 25 - 20900 MONZA（Italy)

Reference Documentation

Ref	Link
Arduino IDE (Desktop)	https://www.arduino.cc/en/Main/Software
Arduino Courses	https://www.arduino.cc/education/courses
Arduino Documentation	https://docs.arduino.cc/
Arduino IDE (Cloud)	https://create.arduino.cc/editor
Cloud IDE Getting Started	https://docs.arduino.cc/cloud/web-editor/tutorials/getting-started/getting-started-web-editor
Project Hub	https://projecthub.arduino.cc/
Library Reference	https://github.com/arduino-libraries/
Online Store	https://store.arduino.cc/

Revision History

Date	Revision	Changes
17/06/2025	4	Nomenclature updates
23/05/2025	3	Fixed pinout table and power info
21/05/2025	2	Fixed info on LEDs
14/05/2025	1	First release